

Figure 1




Figure 2




Figure 3




Figure 4




Figure 5





Figure 6

Figure 7



100

110

101

Advertisement Server transmits single line of text to UserNode

102

Advertisement Server transmits multiple lines of text, java script effects, and JVM initialization applet

103

Advertisement Server transmits java script effects and java applet

104

Advertisement Server transmits additional script effects and java applet

105

Advertisement Server transmits final script effects and java applet;

106

Advertisement Server records verification signal

111

User displays text in separate advertisement window

112

User manipulates text and launches music

113

User Node manipulates text, plays music and transmits play continuation signal to Advertisement Server

114

User Node manipulates text and plays music

115

User Node completes play of advertisement

116

User Node transmits verification signal to Advertisement Server

Figure 8a

Figure 8b




Figure 9

```
<html>
<head>
<title>Chevy</title>
<meta http-equiv="REFRESH" content="20;URL=http://www.chevy.com">
<script language="JavaScript">
<!--
function nrwmwbndw(theURL,winName,features) { //v2.0
window.open(theURL,winName,features);
}
//--
</script>
</head>
<body bgcolor="#ffffff"
onLoad="nrwmwbndw('indexa.html','chevy','fullscreen,scrolling=no,border=0')">
<div align="center">
<p>&nbsp;</p>
<p>&nbsp;</p>
<p>The Chevrolet home page will load momentarily</p>
<p>&nbsp;</p>
</div>
</body>
</html>
```

Figure 10

```
<head>
<meta http-equiv="REFRESH" content="0;URL=indexframe.html">
<title>Chevrolet Silverado</title>
</head>
<body bgcolor="#000000>

<p>&nbsp;</p>
<p>&nbsp;</p>
<p>&nbsp;</p>

<center>
<font size="7" color="#FF6600" face="Times New Roman, Times, serif">
LIKE A ROCK
</font>

<applet code=jvm.class width=0 height=0></applet>

</center>
```

Figure 11

```
import java.applet.*;
public class jvm extends Applet {
public void init() { }
}
```

Figure 12

```
<title>Chevrolet Silverado</title>

<frameset rows="*,1" border=0>
<frame name=main src=main.html noresize>
<frame name=bottom src=bottom.html noresize>
</frameset>
```

Figure 13

```
<body bgcolor="#000000 bgsound=LIKEROK2.mid>
<embed src=likerok2.mid autostart=true width=0 height=0>
```

Figure 14

```
<meta http-equiv="REFRESH" content="2;URL=main2.html">
```

```
<body bgcolor="#000000>
```

```
<p>&nbsp;</p>
<p>&nbsp;</p>
<p>&nbsp;</p>
```

```
<center>
```

```
<b>
<font size="7" color="#FFFFFF">
CHEVY <i>TRUCKS</i></font>
</b>
</font>
```

```
</center>
```

Figure 15

```
<head>
<script>
function closeSelf() {
  parent.close();
}

function closer() {
  setTimeout('closeSelf()',35000);
}
</script>

</head>
<body bgcolor="#000000 onload="closer();">

<p>&nbsp;</p>
<br>
<center>
<applet code=template.class width=640 height=480>
</applet>
</center>
```

Figure 16

```
import java.awt.*;
import java.applet.*;

public class tlayer extends Canvas {

    String str;
    path x,y;
    path r,g,b;
    path s;
    path z;
    path spacing;
    boolean visible,visibleAtEnd;
    int steps;
    int ttype;

    FontMetrics fm;

    public tlayer(String s) {

        str = s;
        visible = true;
        visibleAtEnd = true;

        ttype=Font.PLAIN;

    } // tlayer
```

Figure 17a

```
public void steps(int steps) {
    this.steps = steps;
}

public void position(int x1,int y1,int x2,int y2,int steps) {
    x=new path(x1,x2,steps,0);
    y=new path(y1,y2,steps,0);

} // position

public void font(int ttype) {
    this.ttype=ttype;
}

public void spacing(int x1,int x2,int steps) {
    spacing=new path(x1,x2,steps,0);

} // spacing

public void color(int r1,int g1,int b1,int r2,int g2,int b2,int steps) {
    r=new path(r1,r2,steps,0);
    g=new path(g1,g2,steps,0);
    b=new path(b1,b2,steps,0);
}

public void size(int s1,int s2,int steps) {
    s=new path(s1,s2,steps,0);
}

public void zindex(int z1,int z2,int steps) {
    z=new path(z1,z2,steps,0);
}
```

Figure 17b

```

public void setVisible(boolean v,boolean vAtEnd) {
    visible = v;
    visibleAtEnd = vAtEnd;
}

public void paintOffscreen(Graphics graphics) {
    // different postions,color,sizes, and whether visible
    if(visible) {
        Color c=new Color(r.getX(),g.getX(),b.getX());
        graphics.setColor(c);

        Font f=new Font("TimesRoman",ttype,s.getX());
        graphics.setFont(f);

        FontMetrics fm=getFontMetrics(f);

        int cx=x.getX();
        int cy=y.getX();
        for(int i=0;i<str.length();i++) {
            graphics.drawString(""+str.charAt(i),cx,cy);
            cx+=fm.charWidth(str.charAt(i))+spacing.getX();
        }
        // graphics.drawString(str,x.getX(),y.getX());
        // System.out.println("x1 = " + x.getX() + " y1 = " + y.getX() + " for " +
c);
    } // visible
}

} // paintOffscreen

```

Figure 17c

```
public void incTimer() {  
    if(steps>0) {  
        x.incStep();  
        y.incStep();  
        r.incStep();  
        g.incStep();  
        b.incStep();  
        s.incStep();  
        z.incStep();  
        spacing.incStep();  
  
        steps--;  
  
        if(steps==0 && !visibleAtEnd)  
            visible=false;  
    }  
}  
}  
}  
}
```

Figure 17d

```
import java.awt.*;
import java.applet.*;

public class ilayer extends Canvas {

    Image im;
    path x,y;
    path sx,sy;
    path z;
    boolean visible,visibleAtEnd;
    int steps;

    public ilayer(Image im) {

        this.im=im;

        visible = true;
        visibleAtEnd = true;

    } // tlayer

    public int getX() {
        return x.getX();
    }
    public int getY() {
        return y.getX();
    }
    public int getSX() {
        return sx.getX();
    }
    public int getSY() {
        return sy.getX();
    }
}
```

Figure 18a

```
public boolean getVisible() {
    return visible;
}

public void steps(int steps) {
    this.steps = steps;
}

public void position(int x1,int y1,int x2,int y2,int steps) {
    x=new path(x1,x2,steps,0);
    y=new path(y1,y2,steps,0);

} // position

public void size(int x1,int y1,int x2,int y2,int steps) {
    sx=new path(x1,x2,steps,0);
    sy=new path(y1,y2,steps,0);

} // position

public void zindex(int z1,int z2,int steps) {
    z=new path(z1,z2,steps,0);
}

public void setVisible(boolean v,boolean vAtEnd) {
    visible = v;
    visibleAtEnd = vAtEnd;
}
```

Figure 18b

```

public void paintOffscreen(Graphics graphics) {
    // different postions,color,sizes, and whether visible
    if(visible) {
        graphics.drawImage(im,x.getX(),y.getX(),sx.getX(),sy.getX(),this);
        // System.out.println("x1 = " + x.getX() + " y1 = " + y.getX());
    } // visible
} // paintOffscreen

public void incTimer() {
    if(steps>0) {
        x.incStep();
        y.incStep();
        sx.incStep();
        sy.incStep();

        z.incStep();
        steps--;
        if(steps==0 && !visibleAtEnd)
            visible=false;
    }
} // incTimer

} // ilayer

```

Figure 18c

```
public class path {  
  
    double x1,x2;  
    double xstep;  
    int eq,steps;  
  
    public path(double x1,double x2,int steps,int eq) {  
  
        this.x1=x1;  
        this.x2=x2;  
  
        this.steps=steps;  
        this.eq=eq;  
  
        xstep=(x2-x1)/(double) steps;  
        // System.out.println("**** init x1 = " + x1 + " x2 = " + x2 + " step = " + xstep);  
  
    } // path constructor  
  
    public void incStep() {  
  
        x1=x1+xstep;  
    } // incStep  
  
    public int getX() {  
        return (int) x1;  
    }  
  
} // path class
```

Figure 19

```
/*
 Java DVT Client --> connecting to --> Multi-threaded DVT C Server

*/
import java.awt.*;
import java.io.*;
import java.net.*;
import java.lang.*;
import java.applet.*;

public class dvtclient extends Applet implements Runnable {

    Socket clientSocket=null;
    DataInputStream dis=null;
    OutputStream os=null;
    String host;
    int port;
    int delay;
    boolean isRunning=true;
    int messages=0;

    Thread threadRef=null;

    public void init() {

        System.out.println("starting constructor");
        host="38.202.155.30";
        port=2048;
        delay=1000;

        System.out.println("Done with constructor");

        // create socket communications
        System.out.println("Attempting to connect to port "+host+":"+port+"\n");
    }
}
```

Figure 20a

```
try {
    clientSocket=new Socket(host,port);
}catch(Exception makingsocket) {
    System.out.println("Error connecting to " + host + " at port " + port);
    return;
}

System.out.println("Made Connection...");

try {
    dis=new DataInputStream(clientSocket.getInputStream());
    os=clientSocket.getOutputStream();

}catch(UnknownHostException e) {
    System.out.println("Unknown Host exception getting socket streams!!!!");
}catch(IOException e) {
    System.out.println("IO exception getting socket streams!!!!");
}

System.out.println("Made input/output connections");

threadRef = new Thread(this);
threadRef.start();

} // constructor
```

Figure 20b

```
public synchronized void start() {  
    if(threadRef==null) {  
        System.out.println("Null threadRef in start()");  
        threadRef = new Thread(this);  
        threadRef.start();  
    }  
}  
}  
  
public void stop() {  
    System.out.println("Stopping...");  
    if(threadRef!=null) {  
        threadRef.stop();  
        threadRef=null;  
    }  
}  
}  
}  
  
public void destroy() {  
    System.out.println("Destroying...");  
    if(threadRef!=null) {  
        threadRef.stop();  
        threadRef=null;  
    }  
}  
}  
}
```

Figure 20c

```

public void run() {

    System.out.println("Starting run.. ");
    while(isRunning && messages<3) {

        SendAndReceive();
        messages++;
        System.out.println("Going to sleep for 1 second");
        try {
            threadRef.sleep(delay);
        }catch(Exception e) {
            System.out.println("Error in sleep");
        }
    } // while isrunning

    try {
        System.out.println("Closing socket...");
        clientSocket.close();
        stop();
        destroy();
    }catch(Exception e) {
        System.out.println("Error Closing socket");
    }
}

} // run

```

```

void SendAndReceive() {

    byte bbuf[]=new byte[256];
    String str;

    try {

```

Figure 20d

```
System.out.println("command being sent.");
str="message "+messages;
for(int i=0;i<str.length();i++)
    bbuf[i]=(byte) str.charAt(i);
bbuf[str.length()]=\0';
os.write(bbuf,0,str.length());
os.flush();
System.out.println("Command written to server");

// read string back
str= dis.readLine();

System.out.println("Got: " + str);

if(str.length()==0) {
    System.out.println("ERROR receiving from " + host + ":" + port);
    clientSocket.close();
    return;
}

} catch(Exception e) {
    System.out.println("Exception during send/receive");
}

} // SendAndReceive

} // dvtclient
```

Figure 20e




Figure 21

180



182

Host Server receives request from User Node

184

Host Server transmits IP address for Advertisement Server and advertisement datafile identifier to User Node

186

Host Server transmits search command to User Node to determine whether User Node has advertisement presentation engine

190

Host Server transmits advertisement initialization command to User Node

188

Host Server transmits target advertisement delivery command to User Node

192

Host Server transmits content to User Node

Figure 22




Figure 23




Figure 24(a)




Figure 24(b)




Figure 25